



V-Probe Factory Reset Key

Software Release Notes

Software version: 20170809

October 13, 2017

Release Scope:

Formal Release. General availability.

Description:

The vprobe_factory.key file is a small utility software designed to reset the V-Probe to its factory default configuration. The V-Probe factory default settings are the following:

IP Configuration: DHCP

V-Perf Compatibility: IPerf3

Port number: 5201

V-Probe Discovery Mode: Local

Installation:

- a. Download the vprobe_factory zip file to your local computer
- b. Unzip file
- c. Copy the vprobe_factory.key file to the root directory of a USB drive
- d. Install the USB drive on one of the USB ports of the V-Probe
- e. Connect DC power to the V-Probe and wait for V-Probe to boot up
- f. The V-Probe is now reconfigured in factory default mode

© 2015 - 2017 VeEX Inc. All rights reserved.

VeEX, VePAL, RXT, MTTplus, ReVeal, Fiberizer, VeExpress, V-SAM, Multi-BERT, V logos, Sunrise Telecom, SunSet, and MTT are trademarks or registered trademarks of VeEX Incorporated, or one of its affiliates. All other trademarks or registered trademarks are the property of their respective owners.

Some features listed in this document require software options that may require paid activation or license, and may or may not be available in all products. VeEX Inc., reserves the right to change, without notice, product offerings or specifications.